

GSM TRI-BAND 900/2170 MHz POWER SPLITTER

- 2 WAY 0° POWER DIVIDER/COMBINER
- IDEAL FOR 900/2170 MHz GSM SYSTEMS
- MULTIPLE ANTENNA FEED
- WEATHER-PROOF HOUSING

This tri-band Power Splitter/Combiner is a universal system building block. It is intended for use in the 900/2170 MHz GSM systems. It can be used to feed multiple antennas in order to reduce the system complexity and to improve the reliability.

Electrical characteristics:

Frequency Band (*)	880 to 960 MHz	1710 to 2170 MHz
Reflection	< -20 dB	< -20 dB
Isolation	> 25 dB	> 25 dB
Insertion Loss	0.2 dB (above theoretical 3 dB)	0.3 dB tip. (max.0.4 above theoretical 3 dB)
Max Input Power	40W@ VSWR< 1.2	40W@ VSWR< 1.2
	2W@ VSWR < 2	2W@ VSWR < 2
	1W@ VSWR >10	1W@ VSWR >10
Connectors	N-female	N-female
Operating Temperature Range	- 30 to + 70°C	- 30 to + 70°C

(*) Other frequency range can be specified

Specifications are subject to change without notice.

Outline dimensions (mm):

